



CFH..MA 类型

预包装润滑脂

螺柱直径 (mm)	类型代号				尺寸 (mm)												基本额定 动负荷	基本额定 静负荷	最大 允许载荷	允许转速 *	轨道载荷能力		最大 拧紧力矩	质量						
	圆筒外圈		球面外圈 R250(CF5),R500(CF6 ~ CF10-1)		D	C	d	G	G1	B1	B2	C1	H	rs 最小	e	f 最小					Cr N	Cor N			N	rpm	圆筒外圈	球面外圈	N-m	g (大约)
	h7公差	无密封圈	带密封圈	无密封圈																							带密封圈	N		
5	0 -0.012	CFH 5MA	CFH 5MUUA	CFH 5MRA	CFH 5MUURA	13	9	5	M5×0.8	7.5	23	13	0.5	2.5	0.3	0.2	9.7	2 880	2 540	1 420	29 000	2 250	530	2	10.5					
		CFH 5VMA	CFH 5VMUUA	CFH 5VMRA	CFH 5VMUURA													4 690	5 060	1 420	11 600									
6	0 -0.012	CFH 6MA	CFH 6MUUA	CFH 6MRA	CFH 6MUURA	16	11	6	M6×1	8	28	16	0.6	3	0.3	0.25	11	3 330	3 330	2 110	25 000	3 430	1 080	3	18.5					
		CFH 6VMA	CFH 6VMUUA	CFH 6VMRA	CFH 6VMUURA													6 400	7 840	2 110	12 000									
8	0 -0.015	CFH 8MA	CFH 8MUUA	CFH 8MRA	CFH 8MUURA	19	11	8	M8×1.25	10	32	20	0.6	4	0.3	0.25	13	3 960	4 330	4 710	20 000	4 020	1 370	8	28.5					
		CFH 8VMA	CFH 8VMUUA	CFH 8VMRA	CFH 8VMUURA													7 470	10 270	4 710	9 000									
10	0 -0.015	CFH10MA	CFH10MUUA	CFH10MRA	CFH10MUURA	22	12	10	M10×1.25	12	36	23	0.6	5	0.3	0.3	15	4 950	6 310	6 860	17 000	4 700	1 670	15	45					
		CFH10VMA	CFH10VMUUA	CFH10VMRA	CFH10VMUURA													8 740	13 340	7 450	7 500									
10	0 -0.015	CFH10-1MA	CFH10-1MUUA	CFH10-1MRA	CFH10-1MUURA	26	12	10	M10×1.25	12	36	23	0.6	5	0.3	0.3	15	4 950	6 310	6 860	17 000	5 490	2 060	15	60					
		CFH10-1VMA	CFH10-1VMUUA	CFH10-1VMRA	CFH10-1VMUURA													8 740	13 340	7 450	7 500									

* 无密封圈，适合润滑脂润滑。如果是油润滑，最大允许值可到该数值的 130%。
若为密封型，数值为该数值的 70%。

外圈公差 (μm)

类型	圆筒外圈	球面外圈
CF5M,CF6M	0/-8	0/-50
CF8M,CF10M,CF10-1M	0/-9	0/-50

附件

类型	附件
CF3M/CF4M/CF5M	不锈钢螺母 已预装
CF6M/CF8M/CF10M/CF10-1M	已预装