



# SEPARABLE NEEDLE ROLLER BEARINGS

WITH INNER RING



NAF

NAFW



NAF

NAFW


## NAF(W) TYPE

Shaft Diameter (mm)	Designation	Dimensions (mm)						Standard mounting dimensions (mm)			Basic dynamic load rating	Basic static load rating	Limiting speed*	Mass	Usable bearing designation		
		d	D	C	r's min	F	db	Da MAX	da						Db	Cr N	Cor N
	NAF(W)								MIN	MAX							
<b>6</b>	<b>NAF 61710</b>	6 <sup>0</sup> <sub>-0.008</sub>	17	10	0.3	10	12.4	15	8	9.7	10.4	4 100	4 500	28 000	14	RNAF101710	IR61010
<b>7</b>	<b>NAF 72012</b>	7 <sup>0</sup> <sub>-0.008</sub>	20	12	0.3	10	13.5	18	9	9.7	10.4	6 000	6 000	28 000	23	RNAF102012	IR71012
<b>9</b>	<b>NAF 92212</b>	9 <sup>0</sup> <sub>-0.008</sub>	22	12	0.3	12	17.5	20	11	11.5	12.4	9 000	8 400	26 000	24	RNAF122212	IR91212
<b>10</b>	<b>NAF 102213</b>	10 <sup>0</sup> <sub>-0.008</sub>	22	13	0.3	14	17.6	20	12	13	14.6	7 800	9 400	24 000	26	RNAF142213	IR101413
	<b>NAFW 102220</b>	10 <sup>0</sup> <sub>-0.008</sub>	22	20	0.3	14	17.6	20	12	13	14.6	10 800	14 200	24 000	40	RNAFW142220	IR101420
	<b>NAF 102612</b>	10 <sup>0</sup> <sub>-0.008</sub>	26	12	0.3	14	19.4	24	12	13	14.6	9 800	9 700	24 000	36	RNAF142612	IR101412
<b>12</b>	<b>NAF 122413</b>	12 <sup>0</sup> <sub>-0.008</sub>	24	13	0.3	16	19.6	22	14	15	16.6	8 600	11 000	23 000	30	RNAF162413	IR121613
	<b>NAFW 122420</b>	12 <sup>0</sup> <sub>-0.008</sub>	24	20	0.3	16	19.6	22	14	15	16.6	11 900	16 700	23 000	45	RNAFW162420	IR121620
	<b>NAF 122812</b>	12 <sup>0</sup> <sub>-0.008</sub>	28	12	0.3	16	21.4	26	14	15	16.6	10 500	10 900	23 000	40	RNAF162812	IR121612
<b>15</b>	<b>NAF 152813</b>	15 <sup>0</sup> <sub>-0.008</sub>	28	13	0.3	20	23.6	26	17	19	20.6	9 600	13 500	20 000	37	RNAF202813	IR152013
	<b>NAFW 152826</b>	15 <sup>0</sup> <sub>-0.008</sub>	28	26	0.3	20	23.6	26	17	19	20.6	16 500	27 100	20 000	76	RNAFW202826	IR152026
	<b>NAF 153212</b>	15 <sup>0</sup> <sub>-0.008</sub>	32	12	0.3	20	25.4	30	17	19	20.6	12 400	14 300	20 000	51	RNAF203212	IR152012
<b>17</b>	<b>NAF 173013</b>	17 <sup>0</sup> <sub>-0.008</sub>	30	13	0.3	22	25.6	28	19	21	22.6	10 200	15 200	18 000	43	RNAF223013	IR172213
	<b>NAFW 173026</b>	17 <sup>0</sup> <sub>-0.008</sub>	30	26	0.3	22	25.6	28	19	21	22.6	17 600	30 300	18 000	85	RNAFW223026	IR172226
	<b>NAF 173516</b>	17 <sup>0</sup> <sub>-0.008</sub>	35	16	0.3	22	27.8	33	19	21	22.6	17 600	20 900	18 000	77	RNAF223516	IR172216
	<b>NAFW 173532</b>	17 <sup>0</sup> <sub>-0.008</sub>	35	32	0.3	22	27.8	33	19	21	22.6	30 200	41 900	18 000	155	RNAFW223532	IR172232
<b>20</b>	<b>NAF 203517</b>	20 <sup>0</sup> <sub>-0.010</sub>	35	17	0.3	25	29.5	33	22	24	25.6	17 300	26 600	16 000	75	RNAF253517	IR202517
	<b>NAFW 203526</b>	20 <sup>0</sup> <sub>-0.010</sub>	35	26	0.3	25	29.5	33	22	24	25.6	22 500	37 200	16 000	114	RNAFW253526	IR202526
	<b>NAF 203716</b>	20 <sup>0</sup> <sub>-0.010</sub>	37	16	0.3	25	30.4	35	22	24	25.6	19 400	24 500	16 000	80	RNAF253716	IR202516
	<b>NAFW 203732</b>	20 <sup>0</sup> <sub>-0.010</sub>	37	32	0.3	25	30.4	35	22	24	25.6	33 200	49 000	16 000	158	RNAFW253732	IR202532
<b>25</b>	<b>NAF 254017</b>	25 <sup>0</sup> <sub>-0.010</sub>	40	17	0.3	30	34.5	38	27	29	30.6	18 600	31 100	13 000	88	RNAF304017	IR253017
	<b>NAFW 254026</b>	25 <sup>0</sup> <sub>-0.010</sub>	40	26	0.3	30	34.5	38	27	29	30.6	24 200	43 400	13 000	136	RNAFW304026	IR253026
	<b>NAF 254216</b>	25 <sup>0</sup> <sub>-0.010</sub>	42	16	0.3	30	35.4	40	27	29	30.6	20 800	28 300	13 000	94	RNAF304216	IR253016
	<b>NAFW 254232</b>	25 <sup>0</sup> <sub>-0.010</sub>	42	32	0.3	30	35.4	40	27	29	30.6	35 700	56 800	13 000	187	RNAFW304232	IR253032
<b>30</b>	<b>NAF 304517</b>	30 <sup>0</sup> <sub>-0.010</sub>	45	17	0.3	35	39.5	43	32	34	35.6	20 500	36 900	11 000	100	RNAF354517	IR303517
	<b>NAFW 304526</b>	30 <sup>0</sup> <sub>-0.010</sub>	45	26	0.3	35	39.5	43	32	34	35.6	26 600	51 600	11 000	155	RNAFW354526	IR303526
	<b>NAF 304716</b>	30 <sup>0</sup> <sub>-0.010</sub>	47	16	0.3	35	40.4	45	32	34	35.6	23 000	33 800	11 000	108	RNAF354716	IR303516
	<b>NAFW 304732</b>	30 <sup>0</sup> <sub>-0.010</sub>	47	32	0.3	35	40.4	45	32	34	35.6	39 500	67 800	11 000	215	RNAFW354732	IR303532

\* Suitable for oil lubrication. In case of grease lubrication, down to 50% of this value.


# SEPARABLE NEEDLE ROLLER BEARINGS

WITH INNER RING



NAF

NAFW



NAF

NAFW

## NAF(W) TYPE

Shaft Diameter (mm)	Designation	Dimensions (mm)							Standard mounting dimensions (mm)			Basic dynamic load rating	Basic static load rating	Limiting speed*	Mass	Usable bearing designation					
		d	D	C	r/s min	F	db	Da MAX	da		Db					Cr N	Cor N	rpm	g (approx)	OUTER RING	INNER RING
									MIN	MAX											
35	NAF 355017	35	50	17	0.3	40	43.5	48	37	39	40.8	22 200	42 700	10 000	115	RNAF405017	IR354017				
	NAFW 355034	35 <sub>0</sub>	50	34	0.3	40	43.5	48	37	39	40.8	38 000	85 300	10 000	230	RNAFW405034	IR354034				
	NAF 355520	35 <sub>-0.012</sub>	55	20	0.3	40	45.2	53	37	39	40.8	31 500	48 000	10 000	188	RNAF405520	IR354020				
	NAFW 355540	35	55	40	0.3	40	45.2	53	37	39	40.8	53 900	96 000	10 000	375	RNAFW405540	IR354040				
40	NAF 405517	40	55	17	0.3	45	48.5	53	42	44	45.8	23 200	47 200	10 000	129	RNAF455517	IR404517				
	NAFW 405534	40 <sub>0</sub>	55	34	0.3	45	48.5	53	42	44	45.8	39 900	94 200	10 000	255	RNAFW455534	IR404534				
	NAF 406220	40 <sub>-0.012</sub>	62	20	0.3	45	50.9	60	42	44	45.8	33 200	53 300	9 000	236	RNAF456220	IR404520				
	NAFW 406240	40	62	40	0.3	45	50.9	60	42	44	45.8	57 000	106 900	9 000	475	RNAFW456240	IR404540				
45	NAF 456220	45	62	20	0.3	50	54.2	60	47	49	50.8	27 100	59 300	8 000	197	RNAF506220	IR455020				
	NAFW 456240	45 <sub>0</sub>	62	40	0.3	50	54.2	60	49	49.5	50.8	46 400	118 700	8 000	389	RNAFW506240	IR455040				
	NAF 457220	45 <sub>-0.012</sub>	72	20	0.6	55	60.9	68	49	54	55.8	37 400	66 400	7 500	340	RNAF557220	IR455520				
	NAFW 457240	45	72	40	0.6	55	60.9	68	49	54	55.8	64 100	132 400	7 500	685	RNAFW557240	IR455540				
50	NAF 506820	50	68	20	0.6	55	59.5	64	54	54.5	55.8	28 500	66 000	7 500	230	RNAF556820	IR505520				
	NAFW 506840	50 <sub>0</sub>	68	40	0.6	55	59.5	64	54	54.5	55.8	48 900	132 400	7 500	465	RNAFW556840	IR505540				
	NAF 507820	50 <sub>-0.012</sub>	78	20	1	60	66.3	73	55	59	60.8	38 900	71 700	6 500	390	RNAF607820	IR506020				
	NAFW 507840	50	78	40	1	60	66.3	73	55	59	60.8	66 700	143 200	6 500	775	RNAFW607840	IR506040				
55	NAF 558530	55 <sub>0</sub>	85	30	1	65	72	80	60	63	66	59 300	127 500	6 000	680	RNAF658530	IR556530				
	NAFW 558560	55 <sub>-0.015</sub>	85	60	1	65	72	80	60	63	66	102 000	254 000	6 000	1 380	RNAFW658560	IR556560				
60	NAF 609030	60 <sub>0</sub>	90	30	1	70	77	85	65	68	71	61 200	135 300	5 500	740	RNAF709030	IR607030				
	NAFW 609060	60 <sub>-0.015</sub>	90	60	1	70	77	85	65	68	71	104 900	271 600	5 500	1 470	RNAFW709060	IR607060				
65	NAF 659530	65 <sub>0</sub>	95	30	1	75	82	90	70	73	76	63 200	144 200	5 500	800	RNAF759530	IR657530				
	NAFW 659560	65 <sub>-0.015</sub>	95	60	1	75	82	90	70	73	76	108 900	289 300	5 500	1 570	RNAFW759560	IR657560				
70	NAF 7010030	70 <sub>0</sub>	100	30	1	80	87	95	75	78	81	64 900	153 000	5 000	840	RNAF8010030	IR708030				
	NAFW 7010060	70 <sub>-0.015</sub>	100	60	1	80	87	95	75	78	81	111 800	306 000	5 000	1 670	RNAFW8010060	IR708060				
75	NAF 7510530	75 <sub>0</sub> -0.015	105	30	1	85	92	100	80	83	86	66 600	160 800	4 800	890	RNAF8510530	IR758530				
80	NAF 8011030	80 <sub>0</sub> -0.015	110	30	1	90	97	105	85	88	91	69 500	173 600	4 500	930	RNAF9011030	IR809030				
85	NAF 8511530	85 <sub>0</sub> -0.020	115	30	1	95	102	110	90	93	96	70 900	182 400	4 200	970	RNAF9511530	IR859530				
90	NAF 9012030	90 <sub>0</sub> -0.020	120	30	1	100	107	115	95	98	101	72 600	191 200	4 000	1 040	RNAF10012030	IR9010030				

\* Suitable for oil lubrication. In case of grease lubrication, down to 50% of this value.